

# CLEANCERT

## ECOBULK MX CC & ECOBULK MX CC EV

Maximum cleanliness and safety for your filling good.



For use in areas where product safety and technical cleanliness of the packaging are of especial importance:

- Top standard of safety and cleanliness for material, product and production process
- Extensive risk prevention measures in the production process according to HACCP
- All components and production processes are completely free of silicones
- Traceability back to batch and process level

Please do not hesitate to contact us regarding any technical concerns or questions.

**SCHÜTZ**  
PACKAGING SYSTEMS

www.schuetz.net

### MATERIAL

#### Inner bottle

- Extrusion blow-moulded HDPE with EVOH permeation barrier (optional)



- Antistatic outer layer (optional)



- Additional UV and light protection of the filling product (optional)


#### Outer container

- Welded tubular steel grid, galvanized

#### Bottom plate

- To provide stability and to facilitate minimum residual contents from the inner container

### PALLETS (4-way entry)



### CERTIFICATIONS

- UN 31HA1/Y (optional)
- Maximum density 1.9

### CAPACITY

- MX 640  
640 litres (170 gal)
- MX 820  
820 litres (220 gal)
- MX 1000  
1,000 litres (275 gal)
- MX 1250  
1,250 litres (330 gal)

### FILLING OPENING

- DN 150 with screw cap
- DN 225 with screw cap

### OUTLET VALVES


- Screwable butterfly valve DN 50
- Screwable ball valve DN 50

### DIMENSIONS

- MX 640  
1,200 x 800 x 1,000 (L x W x H)
- MX 820  
1,200 x 1,000 x 1,000 (L x W x H)
- MX 1000  
1,200 x 1,000 x 1,160 (L x W x H)
- MX 1250  
1,200 x 1,000 x 1,350 (L x W x H)

### DYNAMIC LOAD

Filled ECOBULK according to the specific weight of the filling goods



### WEIGHT

- MX 1000  
58 kg with steel pallet  
61 kg with plastic pallet  
63 kg with full-plastic-pallet

### STATIC LOAD

Max. 4-high

