

# FOODCERT

## ECOBULK MX FC & ECOBULK MX FC EV

The new standard for food safety.



Ensures compliance with all specified food standards for material, process and product:

- System certification according to FSSC 22000, (Food Safety System Certification, based on ISO 22000 in combination with PAS 223)
- The certification is recognised by the GFSI (Global Food Safety Initiative)
- Safety measures in accordance with HACCP
- Traceability back to batch and process level

Please do not hesitate to contact us regarding any technical concerns or questions.

**SCHÜTZ**  
PACKAGING SYSTEMS

www.schuetz.net

### MATERIAL

#### Inner bottle

- Extrusion blow-moulded HDPE with the EVOH permeation barrier (optional)
- Antistatic outer layer (optional)
- Additional UV and light protection of the filling product (optional)




#### Outer container

- Welded tubular steel grid, galvanized

#### Bottom plate

- To provide stability and to facilitate minimum residual contents from the inner container

### PALLETS (4-way entry)



### CERTIFICATIONS

#### UN 31HA1/Y (optional)

- Maximum density 1.9

#### SCHÜTZ FOODCERT

- System certification for food (FDA included)

### CAPACITY

#### MX 640

- 640 litres (170 gal)

#### MX 820

- 820 litres (220 gal)

#### MX 1000

- 1,000 litres (275 gal)

#### MX 1250

- 1,250 litres (330 gal)

### FILLING OPENING

- DN 150 with screw cap
- DN 225 with screw cap

### OUTLET VALVES

- Screwable butterfly valve DN 50
- Screwable ball valve DN 50

### DIMENSIONS

#### MX 640

- 1,200 x 800 x 1,000 (L x W x H)

#### MX 820

- 1,200 x 1,000 x 1,000 (L x W x H)

#### MX 1000


- 1,200 x 1,000 x 1,160 (L x W x H)

#### MX 1250

- 1,200 x 1,000 x 1,350 (L x W x H)

### DYNAMIC LOAD

Filled ECOBULK according to the specific weight of the filling goods



### WEIGHT

#### MX 1000

- 58 kg with steel pallet
- 61 kg with plastic pallet
- 63 kg with full-plastic pallet

### STATIC LOAD

Max. 4-high

