

MX-EV



www.schuetz.net

ECOBULK MX-EV

Reliable protection from permeation: **ECOBULK with an EVOH barrier.**




With the new EVOH permeation barrier

- Highly effective barrier against gases like oxygen, carbon dioxide, and nitrogen
- Safely protects the filling product from permeation
- Odours or flavours cannot escape

Please do not hesitate to contact us regarding any technical concerns or questions.

MATERIAL

Inner bottle

- Extrusion blow-moulded HDPE with the EVOH permeation barrier 

- Additional UV and light protection of the filling product (optional)


Outer container

- Welded tubular steel grid, galvanized

Bottom plate

- To provide stability and to facilitate minimum residual contents from the inner container

PALLETS (4-way entry)



CERTIFICATIONS

UN 31HA1/Y (optional)

- Maximum density 1.6

SCHÜTZ FOODCERT (optional)

- System certification for food (FDA included)

CAPACITY

MX-EV 1000

- 1,000 litres (275 gal)

FILLING OPENING

- DN 150 with screw cap
- DN 225 with screw cap

OUTLET VALVES


- Screwable butterfly valve DN 50
- Screwable ball valve DN 50

DIMENSIONS

- 1,200 x 1,000 x 1,160 (L x W x H)

DYNAMIC LOAD

Filled ECOBULK according to the specific weight of the filling goods



WEIGHT

MX-EV 1000

- 58 kg with steel pallet
- 61 kg with plastic pallet
- 63 kg with full-plastic-pallet

STATIC LOAD

Max. 4-high

